

EPAS500M19




C2

C1

**C1
TORQUE SENSOR**
Connector: DTM04-4P + WM4P
Terminals: 4x 0460-202-20141
Boot: 202K111-25-0

1 – Orange (+5V)
2 – Green (0V)
3 – White (Sig A)
4 – Black (Sig B)

**C2
MOTOR**
Connector: 80 Amp Skt 32648879229
Terminals: 2x 12048254
Lock: 15344855



1 – Black (Motor -)
2 – Red (Motor +)

Wire Type	As Supplied
Sleeve Type	DR25 / convoluted
Transition Type	-
Ident Type	-
Repair Loops	No
Contraind	No
Tolerance	+10 / -0
Label Position	-
Kevlar String	No
Cap Shields	-
Kynar	No
Cirris	No

DRAWING NOT TO SCALE.
CONNECTORS SHOWN MAY NOT REPRESENT ACTUAL CONNECTORS SPECIFIED.
ALL DIMENSIONS IN MILLIMETERS.
UNLESS OTHERWISE SHOWN, DIMENSION DATUMS ARE CENTER OF TRANSITIONS, FACE OF STRAIGHT CONNECTORS, CONNECTOR CENTRE LINE OF 90 DEGREE CONNECTORS AND HOLE CENTRE LINE OF RING TERMINALS.
CLOCKING OF 90 DEGREE BOOTS REFERS TO CONNECTOR FACE, KEYWAY AT 12 O'CLOCK, LOOM LEG BEHIND SHOWS TIME.

CUSTOMER:	DCE		REVISION:
TITLE:	EPAS500M19		
PART NO:	EPAS500M19		
DRAWN BY:	D.Cunliffe	DATE:	2 nd Aug 2021
CHECKED BY:		DATE:	
FILENAME:	EPAS500M19 Drawing- - Customer.vsd		

